

Tire Charts 2013 Utility Vehicles, Trucks, Busses, Cargo



Tire / Rim Size	Filling amount		Tire / Rim Size	Filling amount		Tire / Rim Size	Filling amount	
	Liter	strokes		Liter	strokes		Liter	strokes
9 Zoll			19.5 Zoll			20.5 Zoll		
6.00 R	0,36	3	18.00 R	2,95	24	525 / 65	3,20	26
10 Zoll			19.5 R	3,30	26	24 R	4,70	38
225 / 75 R	0,67	5	225 / 70 R	0,90	7	21 Zoll		
12 Zoll			245 / 70 R	1,00	8	24 R	4,75	38
7.00 R	0,53	4	265 / 70 R	1,15	9	22.5 Zoll		
15 Zoll			285 / 70 R	1,30	10	8 R - 9 R	1,21	10
7.50 R	0,66	5	305 / 70 R	1,40	11	10 R	1,25	10
8.25 R	0,76	6	425 / 55 R	2,05	16	11 R	1,50	12
9.00 R	0,86	7	435 / 50 R	2,00	16	12 R	1,70	14
10.00 R	1,00	8	445 / 65 R	2,40	19	13 R	1,85	15
205 / 80 R	0,73	6	445 / 45 R	2,00	16	15 R	2,30	22
16 Zoll			20 Zoll			18 R	3,00	24
7.00 R	0,62	5	7.00	0,70	6	255 / 70 R	1,20	10
7.50 R	0,68	5	7.50	0,80	6	255 / 80 R	1,25	10
8.25 R	0,80	6	8.25	0,90	7	275 / 70 R	1,37	11
9.00 R	0,90	7	9.00	1,00	8	275 / 80 R	1,40	11
11.00 R	1,20	10	10.00	1,20	10	285 / 60 R	1,30	10
17.5 Zoll			11.00	1,35	11	295 / 60 R	1,40	11
7 R	0,65	5	8.25	0,90	7	295 / 80 R	1,60	13
8 R	0,80	6	9.00	1,00	8	305 / 70 R	1,50	12
8.5 R	0,90	7	10.00	1,38	11	305 / 60 R	1,50	12
9.5 R	1,00	8	11.00	1,35	11	315 / 60 R	1,50	12
10 R	1,10	9	11.00	1,35	11	315 / 70 R	1,50	12
205 / 65 R	0,72	6	11.50	1,45	12	315 / 75 R	1,70	14
205 / 75 R	0,76	6	12.00	1,55	12	315 / 80 R	1,88	15
215 / 75 R	0,82	7	12.5 R	1,65	13	385 / 55 R	2,00	16
225 / 75 R	0,88	7	13.00 R	1,75	14	385 / 65 R	2,10	17
235 / 75 R	0,93	7	14.00 R	2,00	16	395 / 60 R	2,12	17
235 / 75 R	0,93	7	15.5 / 80	2,30	18	425 / 65 R	2,40	19
245 / 70 R	0,96	8	16.00 R	2,40	19	435 / 50 R	2,40	19
265 / 70 R	1,10	9	275 / 80	1,30	10	445 / 65 R	2,63	21
19.5 Zoll			335 / 80	1,75	14	445 / 75 R	3,00	24
8.00 R	0,85	7	365 / 85	2,10	17	495 / 45 R	2,50	20
9,5	1,10	9	365 / 80	2,00	16	500 / 45 R	2,6	23
16.5 R	2,50	20	385 / 80	2,20	18	24 Zoll		
18.00 R	2,90	23	395 / 85	2,40	19	12.00 R	1,88	15

For all dimensions, Highway, light Off-Road; recycling Roadworks tunneling use **AirSeal HD Spezial** or **AirSeal HD**

The filling amounts are calculated for mixed operation between street - building site

For street use only, the filling amount can be reduced by 20%

For operation on waste depots etc., we suggest to increase the filling amount considerably

The filling amounts are stated in full Pumps strokes, one Stroke is **1/8 Liters**, ore **125 ml**

Therefore **8 full strokes** are **1 Liter**.

The notches on the Piston rod are marking 1 US Fluid Ounces or 30 ml or 0,03 Liters ;

The high pressure pump enables the precise filling of Tyres without deflating.

AirSeal (Europa) VertriebsgmbH 1230 Wien Karl-Sarg-Gasse 3 Tel. 0664 125 63 48